

HD-134B



1.3 Megapixel 960P Water-proof IR HD Camera



***THE PERFECT
CHOICE FOR
PROFESSIONALS***

Key Features

- 1/3" 1.3 Megapixel CMOS
- 25/30/50/60fps@960P
- High speed, long distance real-time transmission
- HD and standard definition switchable
- OSD Menu, control over coaxial cable
- Day/Night(ICR), AWB, AGC, BLC, 3D-DNR
- 3.6mm fixed lens (2.8mm, 4mm, 8mm optional)
- Max. IR LEDs length 20m, Smart IR
- IP66, DC12V

The HD-134B is a HD Bullet Camera that featuring integrated IR illumination LEDs. The HD-134B is capable of delivering high definition video at up to 60 frames per second, with virtually zero lag, using the HD standard on conventional coaxial cable. This camera features Simple Focus, Super Dynamic Range (SDR), and Noise Reduction technology, as well as a True Day Night infrared cut filter, and Wide Dynamic Range rated at 100dB. In addition, it is IP66-rated for indoor or outdoor applications and supplied with a mounting bracket for wall, surface or ceiling mount installation.

HD-134B

Technical Specifications

Model	HD-134B
Camera	
Image Sensor	1/3" 1.3 Megapixel CMOS
Effective Pixels	1280(H)×960(V)
Electronic Shutter	4/25s~1/45,000s
Video Frame Rate	30/60 fps@960P
Synchronization	Internal
Min. Illumination	0.01Lux@F1.2 (AGC ON), 0Lux IR LED on
Video Output	1-channel BNC HD high definition video output/ CVBS standard definition video output (Can switch)
Camera Features	
Max. IR LEDs Length	20m, Smart IR
Day/Night	Auto(ICR) / Color / B/W
Noise Reduction	2D/3D
OSD Menu	Support
Lens	
Focal length	3.6 mm fixed lens (2.8mm, 4mm, 8mm optional)
Mount Type	M12
General	
Power Supply	DC12V±10%
Power Consumption	Max 4.2W
Working Environment	-30°C~+60°C / Less than 95% RH (no condensation)
Transmission Distance	Over 500m via 75 -3 coaxial cable
Ingress Protection	IP66
Dimensions (W×D×H)	130.5 mm×69.4 mm×69.4 mm
Weight	380g