

# HD-135B



## 1.3 Megapixel 960P Water-proof IR HD Camera



**THE *PERFECT*  
CHOICE FOR  
PROFESSIONALS**

### Key Features

- 1/3" 1.3 Megapixel CMOS
- 25/30/50/60fps@960P
- High speed, long distance real-time transmission
- HD and standard definition switchable
- OSD Menu, control over coaxial cable
- Day/Night(ICR), AWB, AGC, BLC, 3D-DNR
- 4mm fixed lens (2.8 mm, 3.6mm, 8mm optional)
- Max. IR LEDs length 50m, Smart IR
- IP66, DC12V

The HD-135B is a discreet general purpose HD camera suitable for a wide range of applications. It incorporates the 6th generation Winner engine that features premium level resolution at 960P in sharp mode and other core functionalities such as 3D-DNR, day & night(ICR), and defog. It can capture images within 50 meters in extremely low or no lighting using its built-in IR LED lamps, the HD-135B would be a perfect solution for who is looking for a cost effective high quality video surveillance camera.

# HD-135B

## Technical Specifications

Model	HD-135B
Camera	
Image Sensor	1/3" 1.3 Megapixel CMOS
Effective Pixels	1280(H)×960(V)
Electronic Shutter	4/25s~1/45,000s
Video Frame Rate	25/30/50/60 fps@960P
Synchronization	Internal
Min. Illumination	0.01Lux@F1.2 (AGC ON), 0Lux IR LED on
Video Output	1-channel BNC HD high definition video output/ CVBS standard definition video output (Can switch)
Camera Features	
Max. IR LEDs Length	50m, Smart IR
Day/Night	Auto(ICR) / Color / B/W
Noise Reduction	2D/3D
OSD Menu	Support
Lens	
Focal length	4mm fixed lens (2.8mm, 3.6mm, 8mm optional)
Mount Type	M12
General	
Power Supply	DC12V±10%
Power Consumption	Max 7.7W
Working Environment	-30°C~+60°C / Less than 95% RH (no condensation)
Transmission Distance	Over 500m via 75 -3 coaxial cable
Ingress Protection	IP66
Dimensions (W×D×H)	200.2mm×89.1mm×80.4mm
Weight	0.45kg